

# K-MV O (NO) D 24 V DC STA VA

Normally open, (NO), directly operated, 24 V DC, standard type VA

**HANSA FLEX**

## Vlastnosti

<b>Elektrické pripojenie</b>	device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket
<b>Popis závit</b>	G thread acc. DIN EN ISO 228-1
<b>Teplota média</b>	max. 80 °C when using water or oils; max. 90 °C when using with air
<b>Krytie</b>	IP 65
<b>max. prevádzkový tlak</b>	7 bar
<b>Tesniaci materiál</b>	FPM
<b>kryt, sedlo ventila</b>	Stainless steel 1.4301
<b>vnútorné diely</b>	Stainless steel



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Standard series in two different versions: Directly operated, Pilot-operated

## Výrobok

Označenie	Závit	MS	A: (mm)	B (mm)	C (mm)	vyhotovenie
K- 07 30 01 42	G 1/8	3,0	70,0	40,0	76,0	2
K- 07 30 01 43	G 1/4	3,0	70,0	40,0	76,0	2
K- 07 30 01 44	G 3/8	5,0	85,0	52,0	92,0	2
K- 07 30 01 45	G 1/2	5,0	85,0	52,0	92,0	2