

LKM IR ST DK

Násuvná spojka, hrdlo (vzduch) s poistkou

HANSA FLEX

Vlastnosti

Konštrukcia	Hrdlo rýchlospojky
Prípojka 1	Vnútorý závit BSP, valcový
Prípojka 2	
Prevádzkový tlak	max. 12 bar
Prietok vzduch	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Teplota média	-20 °C to +70 °C
Kryt	Aluminium, anodised
závit	Nickel-plated brass
vnútorné diely	Stainless steel
gombík, ventil	Hardened, galvanised steel
Tesniaci materiál	NBR



Poznámka

Not suitable for hitting / pulsating tools.

Ďalšie údaje na vyžiadanie.

Popis

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Výrobok

Označenie	Prípojovací závit	Prípojka	Dĺžka (mm)	SW (mm)
LKM 06 IR ST DK	G 1/4" -19	G 1/4 female	71,5	21
LKM 10 IR ST DK	G 3/8" -19	G 3/8 female	75,5	21
LKM 13 IR ST DK	G 1/2" -14	G 1/2 female	77,5	24