

# LKM IR ST DK

Násuvná spojka, hrdlo (vzduch) s poistkou

**HANSA FLEX**

## Vlastnosti

|                   |   |
|-------------------|---|
| Konštrukcia       | Hrdlo rýchlospojky                            |
| Prípojka 1        | Vnútorý závit BSP, valcový                    |
| Prípojka 2        |   |
| Prevádzkový tlak  | max. 12 bar                                   |
| Prietok vzduch    | 1.800 l/min (at 6 bar and $\Delta p = 1$ bar) |
| Teplota média     | -20 °C to +70 °C                              |
| Kryt              | Aluminium, anodised                           |
| závit             | Nickel-plated brass                           |
| vnútorné diely    | Stainless steel                               |
| gombík, ventil    | Hardened, galvanised steel                    |
| Tesniaci materiál | NBR   |



## Poznámka

Not suitable for hitting / pulsating tools.

Ďalšie údaje na vyžiadanie.

## Popis

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

## Výrobok

| Označenie       | Prípojovací závit | Prípojka     | Dĺžka (mm) | SW (mm) |
|-----------------|-------------------|--------------|------------|---------|
| LKM 06 IR ST DK | G 1/4" -19        | G 1/4 female | 71,5       | 21      |
| LKM 10 IR ST DK | G 3/8" -19        | G 3/8 female | 75,5       | 21      |
| LKM 13 IR ST DK | G 1/2" -14        | G 1/2 female | 77,5       | 24      |