

## Lastnosti

|                |                |
|----------------|----------------|
| Način izdelave | rezilni prstan |
| Standard       | DIN 3861       |
| Material:      | med            |



## Navodilo

Za navodila za montažo, vgradnjo, obremenitev s tlakom in dovoljene temperature delovanja si, prosimo, oglejte tehnične podatke za navojne cevne priključke.

## Artikel

| Opis         | Serijska | Ø d2<br>(mm) | L1<br>(mm) |
|--------------|----------|--------------|------------|
| SRD 04 LL MG | LL       | 4            | 6,0        |
| SRD 05 LL MG | LL       | 5            | 7,0        |
| SRD 06 LL MG | LL       | 6            | 7,0        |
| SRD 08 LL MG | LL       | 8            | 7,0        |
| SRD 10 LL MG | LL       | 10           | 7,0        |
| SRD 12 LL MG | LL       | 12           | 7,5        |
| SRD 06 MG    | L / S    | 6            | 9,5        |
| SRD 08 MG    | L / S    | 8            | 9,5        |
| SRD 10 MG    | L / S    | 10           | 10,0       |
| SRD 12 MG    | L / S    | 12           | 10,0       |
| SRD 14 MG    | S        | 14           | 10,0       |
| SRD 15 MG    | L        | 15           | 10,0       |
| SRD 16 MG    | S        | 16           | 10,5       |
| SRD 18 MG    | L        | 18           | 10,0       |
| SRD 20 MG    | S        | 20           | 12,5       |
| SRD 22 MG    | L        | 22           | 10,5       |
| SRD 25 MG    | S        | 25           | 12,5       |
| SRD 28 MG    | L        | 28           | 10,5       |
| SRD 30 MG    | S        | 30           | 13,0       |
| SRD 35 MG    | L        | 35           | 13,0       |
| SRD 38 MG    | S        | 38           | 13,5       |
| SRD 42 MG    | L        | 42           | 13,0       |

serijska: LL = zelo lahko L = lahko S = težko – PN = nazivni tlak PB = maks. obratovalni tlak – Ø d2 = zunanji premer cevi

## Variante izdelka

|        |                                |
|--------|--------------------------------|
| SRD    | Rezilni prstan, jeklo          |
| SRD VA | Rezilni prstan, nerjavno jeklo |