

### Lastnosti

|                         |                       |
|-------------------------|-----------------------|
| <b>Priključek 1</b>     | notranji navoj UN/UNF |
| <b>Način izdelave</b>   | protimatica           |
| <b>Standard</b>         | ISO 8434-2            |
| <b>Material:</b>        | jeklo                 |
| <b>Zaščita površine</b> | galvanično prevlečeno |



### Artikel

| Opis             | G1             | L1<br>(mm) | SW<br>(mm) |
|------------------|----------------|------------|------------|
| <b>KM 04 UNF</b> | 7/16" -20 UNF  | 6,4        | 17         |
| <b>KM 05 UNF</b> | 1/2" -20 UNF   | 6,4        | 19         |
| <b>KM 06 UNF</b> | 9/16" -18 UNF  | 6,9        | 22         |
| <b>KM 08 UNF</b> | 3/4" -16 UNF   | 7,9        | 24         |
| <b>KM 10 UNF</b> | 7/8" -14 UNF   | 9,1        | 30         |
| <b>KM 12 UNF</b> | 1.1/16" -12 UN | 10,4       | 36         |
| <b>KM 16 UNF</b> | 1,5/16" -12 UN | 10,4       | 41         |
| <b>KM 20 UNF</b> | 1,5/8" -12 UN  | 10,4       | 50         |
| <b>KM 24 UNF</b> | 1,7/8" -12 UN  | 10,4       | 55         |
| <b>KM 32 UNF</b> | 2,1/2" -12 UN  | 10,4       | 70         |

SW = ključna širina