

WEO VS S

WEO-zapiralni vtič

Lastnosti

| | |
|-------------------------|-----------------------------------|
| Priključek 1 | vtič WEO |
| Oblika tesnila 1 | s O-tesnilom zatesnjen priključek |
| Material: | jeklo |
| Zaščita površine | galvanično prevlečeno |



Artikel

| Opis | Velikost | Obratovalni tlak bar | Ø D1 (mm) | Ø D2 (mm) | L1 (mm) | L2 (mm) |
|--------------------|----------|----------------------|-----------|-----------|---------|---------|
| WEO VS 10 S | 1/4" | PN 350 | 10 | 12,0 | 43,0 | 19,0 |
| WEO VS 13 S | 3/8" | PN 350 | 13 | 16,0 | 50,0 | 22,0 |
| WEO VS 16 S | 1/2" | PN 350 | 16 | 19,0 | 50,0 | 22,0 |
| WEO VS 23 S | 3/4" | PN 350 | 23 | 25,0 | 59,0 | 31,0 |
| WEO VS 30 S | 1" | PN 250 | 30 | 33,0 | 75,0 | 38,5 |

Nadomestni deli

| | |
|-------------------------|------------------------|
| WEO S DEMORING | Obroč za demontažo WEO |
| WEO S M ANSCHLAG | Naslon za montažo WEO |