

T BL

Bločna spojnica SAE, izvedba T

HANSA FLEX

Lastnosti

| | |
|------------------------|--------------------------------|
| Tlačna vrsta | 6000 psi |
| Standard | SAE J 518 C ISO 6162 |
| Oblika izdelave | izvedba T |
| Način izdelave | blok prirobnica SAE |
| Pritrditev | notranji navoj za metr. vijake |
| Material: | S355J2G3 (ST52.3) |



Artikel

| Opis | PB 10.9 (bar) | Velikost | Ø B (mm) | C (mm) | D (mm) | E1 (mm) | E2 (mm) | F (mm) | G (mm) | M metr. |
|---------------------|------------------|----------|-------------|-----------|-----------|------------|------------|-----------|-----------|---------|
| T BL 602-602 | 400 | 3/4" | 19 | 50,8 | 72 | 23,8 | 23,8 | 72 | 55 | M 10 |
| T BL 603-603 | 400 | 1" | 23 | 57,2 | 82 | 27,8 | 27,8 | 82 | 64 | M 12 |
| T BL 604-604 | 400 | 1.1/4" | 30 | 66,7 | 100 | 31,8 | 31,8 | 92 | 72 | M 14 |
| T BL 605-605 | 400 | 1.1/2" | 38 | 79,4 | 110 | 36,5 | 36,5 | 98 | 98 | M 16 |
| T BL 606-606 | 400 | 2" | 50 | 96,8 | 133 | 44,5 | 44,5 | 140 | 105 | M 20 |

PN = nazivni tlak PB = maks. obratovalni tlak