


# T BL

Bločna spojnica SAE, izvedba T

**HANSA FLEX**

## Lastnosti

<b>Tlačna vrsta</b>	6000 psi
<b>Standard</b>	SAE J 518 C ISO 6162
<b>Oblika izdelave</b>	izvedba T
<b>Način izdelave</b>	blok prirobnica SAE
<b>Pritrditev</b>	notranji navoj za metr. vijake
<b>Material:</b>	S355J2G3 (ST52.3)



## Artikel

Opis	PB 10.9 (bar)	Velikost	Ø B (mm)	C (mm)	D (mm)	E1 (mm)	E2 (mm)	F (mm)	G (mm)	M metr.
<b>T BL 602-602</b>	400	3/4"	19	50,8	72	23,8	23,8	72	55	M 10
<b>T BL 603-603</b>	400	1"	23	57,2	82	27,8	27,8	82	64	M 12
<b>T BL 604-604</b>	400	1.1/4"	30	66,7	100	31,8	31,8	92	72	M 14
<b>T BL 605-605</b>	400	1.1/2"	38	79,4	110	36,5	36,5	98	98	M 16
<b>T BL 606-606</b>	400	2"	50	96,8	133	44,5	44,5	140	105	M 20

PN = nazivni tlak PB = maks. obratovalni tlak