


WFG (3000 PSI)

Adapter za spojko SAE, kovani

Lastnosti

Tlačna vrsta	3000 psi
Standard	DIN 3901 / 3902
Način izdelave-dodatek	kovano
Oblika izdelave	koleno 90°
Način izdelave	adapter SAE-prirobnica
Obseg dobave	samo prirobnica
Material:	S355J2G3 (ST52.3)
Zaščita površine	galvanično prevlečeno



Navodilo

Navedeni najvišji obratovalni tlak velja za prirobnico! Dejanski obratovalni tlak se določa na osnovi cevi (debeline stene) in na osnovi kvalitete cevi!

Priporočeni vijaki so navedeni v stolpcih M (metr) ali M (unc).

Artikel

Opis	Serijska	Ø RAD (mm)	PB 10.9 (bar)	Velikost	A	B1 (mm)	B2 (mm)	F1 (mm)	l (mm)	S1 (mm)	S2 (mm)	S3 (mm)	L (mm)	M metr.
WFG 3001/L 15	L	15	315	1/2"	M22x1,5	12	11	66,8	7,0	39	29,0	44	8,7	M 8 x 25
WFG 3002/L 18	L	18	315	3/4"	M26x1,5	15	19	73,9	7,5	42	31,5	48	10,7	M 10 x 35
WFG 3002/L 22	L	22	160	3/4"	M30x2	19	19	75,9	7,5	42	33,5	50	10,7	M 10 x 35
WFG 3003/L 28	L	28	160	1"	M36x2	24	25	82,2	7,5	45	36,5	53	10,7	M 10 x 35
WFG 3004/L 35	L	35	160	1.1/4"	M45x2	30	27	104,3	10,5	50	46,5	68	*1	*2
WFG 3005/L 42	L	42	160	1.1/2"	M52x2	36	36	118,2	11,0	55	47,0	57	13,5	M 12 x 40
WFG 3001/S 16	S	16	350	1/2"	M24x1,5	12	11	70,8	8,5	39	29,5	48	8,7	M 8 x 25
WFG 3002/S 20	S	20	350	3/4"	M30x2	16	19	79,9	10,5	42	32,5	54	10,7	M 10 x 35
WFG 3002/S 25	S	25	350	3/4"	M36x2	17	19	82,9	12,0	42	33,0	57	10,7	M 10 x 35
WFG 3003/S 25	S	25	315	1"	M36x2	20	25	91,2	12,0	45	38,0	62	10,7	M 10 x 35
WFG 3003/S 30	S	30	315	1"	M42x2	24	25	92,2	13,5	45	36,5	63	10,7	M 10 x 35
WFG 3004/S 25	S	25	250	1.1/4"	M36x2	20	27	103,3	12,0	50	43,0	67	*1	*2
WFG 3004/S 30	S	30	250	1.1/4"	M42x2	25	27	106,3	13,5	50	43,5	70	*1	*2
WFG 3004/S 38	S	38	250	1.1/4"	M52x2	28	27	110,3	16,0	50	43,0	74	*1	*2
WFG 3005/S 38	S	38	200	1.1/2"	M52x2	32	36	128,2	16,0	55	48,0	58	13,5	M 12 x 40

serija: LL = zelo lahko L = lahko S = težko -- PN = nazivni tlak PB = maks. obratovalni tlak -- Ø RAD = zunanji premer cevi

*1) = izbirno 10,5 ali 12,5 -- *2) = izbirno M 10 x 30 ali M 12 x 40

Variante izdelka

WFG M (3000 / 6000 PSI) Adapter za spojko SAE, kovani, z 2 polprirobnicama, kompletom vijakov in O-tesnilom