

WFG M (3000 / 6000 PSI)

Adapter za spojko SAE, kovano

HANSA FLEX

Lastnosti

Standard	DIN 3901 / 3902
Način izdelave-dodatek	kovano
Oblika izdelave	koleno 90°
Način izdelave	adapter SAE-prirobnica
Obseg dobave	z 2 polprirobnicama, kompletom vijakov in O-tesnilom
Material:	S355J2G3 (ST52.3)
Zaščita površine	galvanično prevlečeno



Navodilo

Navedeni najvišji obratovalni tlak velja za prirobnico! Dejanski obratovalni tlak se določa na osnovi cevi (debeline stene) in na osnovi kvalitete cevi!

Artikel

Opis	Tlačna vrsta	Serija	Ø RAD	PB 10.9	Velikost	A	B1	B2	C	D	E	F1	F2	I	S1	S2	S3	L	Vijaki
			(mm)	(bar)			(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
WFG 3001/L 15 M	3000 PSI	L	15	315	1/2"	M22x1,5	12	11	38,1	54,0	17,5	66,8	45,6	7,0	39	29,0	44	8,7	(4 x) M 8 x 25
WFG 3002/L 18 M	3000 PSI	L	18	315	3/4"	M26x1,5	15	19	47,6	64,9	22,2	73,9	51,8	7,5	42	31,5	48	10,7	(4 x) M 10 x 30
WFG 3002/L 22 M	3000 PSI	L	22	160	3/4"	M30x2	19	19	47,6	64,9	22,2	75,9	51,8	7,5	42	33,5	50	10,7	(4 x) M 10 x 30
WFG 3003/L 28 M	3000 PSI	L	28	160	1"	M36x2	24	25	52,4	69,9	26,2	82,2	58,4	7,5	45	36,5	53	10,7	(4 x) M 10 x 30
WFG 3004/L 35 M	3000 PSI	L	35	160	1.1/4"	M45x2	30	27	58,7	79,4	30,2	104,3	72,6	10,5	50	46,5	68	*1	*2
WFG 3005/L 42 M	3000 PSI	L	42	160	1.1/2"	M52x2	36	36	69,9	93,8	35,7	118,2	82,4	11,0	76	56,0	77	13,5	(4 x) M 12 x 40
WFG 3001/S 16 M	3000 PSI	S	16	350	1/2"	M24x1,5	12	11	38,1	54,0	17,5	70,8	45,6	8,5	39	29,5	48	8,7	(4 x) M 8 x 25
WFG 3002/S 20 M	3000 PSI	S	20	350	3/4"	M30x2	16	19	47,6	64,9	22,2	79,9	51,8	10,5	42	32,5	54	10,7	(4 x) M 10 x 30
WFG 3002/S 25 M	3000 PSI	S	25	350	3/4"	M36x2	17	19	47,6	64,9	22,2	82,9	51,8	12,0	42	33,0	57	10,7	(4 x) M 10 x 30
WFG 3003/S 25 M	3000 PSI	S	25	315	1"	M36x2	20	25	52,4	69,9	26,2	91,2	58,4	12,0	45	38,0	62	10,7	(4 x) M 10 x 30
WFG 3003/S 30 M	3000 PSI	S	30	315	1"	M42x2	24	25	52,4	69,9	26,2	92,2	58,4	13,5	45	36,5	63	10,7	(4 x) M 10 x 30
WFG 3004/S 25 M	3000 PSI	S	25	250	1.1/4"	M36x2	20	27	58,7	79,4	30,2	103,3	72,6	12,0	50	43,0	67	*1	*2
WFG 3004/S 30 M	3000 PSI	S	30	250	1.1/4"	M42x2	25	27	58,7	79,4	30,2	106,3	72,6	13,5	50	43,5	70	*1	*2
WFG 3004/S 38 M	3000 PSI	S	38	250	1.1/4"	M52x2	28	27	58,7	79,4	30,2	110,3	72,6	16,0	50	43,0	74	*1	*2
WFG 3005/S 38 M	3000 PSI	S	38	200	1.1/2"	M52x2	32	36	69,9	93,8	35,7	128,2	82,4	16,0	76	56,0	87	13,5	(4 x) M 12 x 40
WFG 6001/S 16 M	6000 PSI	S	16	400	1/2"	M24x1,5	12	12	40,5	56,4	18,2	71,6	47,2	8,5	39	29,4	48	8,7	(4 x) M 8 x 30
WFG 6002/S 16 M	6000 PSI	S	16	400	3/4"	M24x1,5	12	17	50,8	71,3	23,8	85,0	60,0	8,5	48	36,5	55	10,7	(4 x) M 10 x 35
WFG 6002/S 20 M	6000 PSI	S	20	400	3/4"	M30x2	16	17	50,8	71,3	23,8	87,0	60,0	10,5	48	35,5	57	10,7	(4 x) M 10 x 35
WFG 6002/S 25 M	6000 PSI	S	25	400	3/4"	M36x2	17	17	50,8	71,3	23,8	90,0	60,0	12,0	48	36,0	60	10,7	(4 x) M 10 x 35
WFG 6003/S 25 M	6000 PSI	S	25	400	1"	M36x2	20	24	57,2	81,0	27,8	99,8	69,0	12,0	60	41,0	65	13,0	(4 x) M 12 x 45
WFG 6003/S 30 M	6000 PSI	S	30	400	1"	M42x2	24	24	57,2	81,0	27,8	102,9	69,0	13,5	60	41,5	68	13,0	(4 x) M 12 x 45
WFG 6004/S 30 M	6000 PSI	S	30	400	1.1/4"	M42x2	25	31	66,7	95,2	31,8	109,6	77,2	13,5	68	44,5	71	14,7	(4 x) M 14 x 50
WFG 6004/S 38 M	6000 PSI	S	38	350	1.1/4"	M52x2	28	31	66,7	95,2	31,8	114,6	77,2	16,0	68	45,0	76	14,7	(4 x) M 14 x 50
WFG 6004/S 38-400 M	6000 PSI	S	38	400	1.1/4"	M52x2	22	24	66,7	95,2	31,8	114,5	77,2	16,0	68	45,0	76	14,7	(4 x) M 14 x 50
WFG 6005/S 38 M	6000 PSI	S	38	350	1.1/2"	M52x2	30	36	79,4	112,8	36,5	134,5	95,0	16,0	76	56,0	87	17,0	(4 x) M 16 x 55

serija: LL = zelo lahko L = lahko S = težko - PN = nazivni tlak PB = maks. obratovalni tlak - Ø RAD = zunanji premer cevi

*1) = izbirno 10,5 ali 12,5 - *2) = izbirno M 10 x 30 ali M 12 x 40

Variante izdelka

WFG (3000 PSI) Adapter za spojko SAE, kovano, samo prirobnica