

# FHR 91

Zaporni vijak z zunanjo šestkotno glavo

**HANSA FLEX**

## Lastnosti

|                         |   |
|-------------------------|---|
| <b>Priključek 1</b>     | zunanji navoj cilindrični BSP               |
| <b>Oblika tesnila 1</b> | izvedba A                                   |
| <b>Način izdelave</b>   | Zaporni vijaki, z zunanjim šestkotnim robom |
| <b>Oblika izdelave</b>  | ravno                                       |
| <b>Standard</b>         | DIN 910                                     |
| <b>Material:</b>        | jeklo                                       |
| <b>Zaščita površine</b> | galvanično prevlečeno                       |



## Artikel

| Opis         | G1           | i<br>(mm) | D<br>(mm) | L1<br>(mm) | L2<br>(mm) | SW<br>(mm) |
|--------------|--------------|-----------|-----------|------------|------------|------------|
| FHR 91-1/8   | G 1/8" -28   | 8         | 14        | 17         | 6          | 10         |
| FHR 91-1/4   | G 1/4" -19   | 12        | 18        | 21         | 6          | 13         |
| FHR 91-3/8   | G 3/8" -19   | 12        | 22        | 21         | 6          | 17         |
| FHR 91-1/2   | G 1/2" -14   | 14        | 26        | 26         | 8          | 19         |
| FHR 91-5/8   | G 5/8" -14   | 14        | 28        | 26         | 8          | 19         |
| FHR 91-3/4   | G 3/4" -14   | 16        | 32        | 30         | 10         | 24         |
| FHR 91-1     | G 1" -11     | 16        | 39        | 32         | 11         | 27         |
| FHR 91-1 1/4 | G 1,1/4" -11 | 16        | 49        | 33         | 12         | 30         |
| FHR 91-1 1/2 | G 1,1/2" -11 | 16        | 55        | 33         | 12         | 30         |