

Lastnosti

Priključek 1	metrični zunanji navoj konusni
Oblika tesnila 1	tesni navoje
Priključek 2	metrični zunanji navoj, cilindrični
Oblika tesnila 2	24° notranji konus
Način izdelave	uvojni vijačni priključek
Oblika izdelave	koleno 90°
Standard	DIN 2353 ISO 8434-1
Obseg dobave	nastavek (brez prekrivne matice in rezalnega obroča)
Material:	jeklo
Zaščita površine	galvanično prevlečeno



Navodilo

Za navodila za montažo, vgradnjo, obremenitev s tlakom in dovoljene temperature delovanja si, prosimo, oglejte tehnične podatke za navojne cevne priključke.

Artikel

Opis	Seriya	Obratovalni tlak bar	Ø d2 (mm)	G	i (mm)	L4 (mm)	L5 (mm)	L7 (mm)	SW (mm)
XWM 04 LL	LL	PN 100	4	M 8 x 1 K	8,0	11,0	17	15	9
XWM 04 LL 6	LL	PN 100	4	M 6 x 1 K	8,0	11,0	17	15	9
XWM 05 LL	LL	PN 100	5	M 8 x 1 K	8,0	9,5	17	15	9
XWM 06 LL 6	LL	PN 100	6	M 6 x 1 K	7,0	9,5	17	15	9
XWM 06 LL 8	LL	PN 100	6	M 8 x 1 K	8,0	9,5	17	15	9
XWM 06 LL	LL	PN 100	6	M 10 x 1 K	9,0	9,5	17	15	9
XWM 08 LL	LL	PN 100	8	M 10 x 1 K	10,0	11,5	20	17	12
XWM NW 04 HL	L	PN 315	6	M 10 x 1 K	8,0	12,0	20	19	12
XWM NW 04 HL 12	L	PN 315	6	M 12 x 1,5 K	12,0	12,0	22	19	12
XWM NW 06 HL	L	PN 315	8	M 12 x 1,5 K	12,0	14,0	26	21	12
XWM NW 08 HL	L	PN 315	10	M 14 x 1,5 K	11,5	15,0	27	22	14
XWM NW 08 HL 16	L	PN 315	10	M 16 x 1,5 K	11,5	15,0	28	22	14
XWM NW 10 HL	L	PN 315	12	M 16 x 1,5 K	11,5	17,0	28	24	17
XWM NW 13 HL	L	PN 315	15	M 18 x 1,5 K	13,5	21,0	32	28	19
XWM NW 16 HL	L	PN 315	18	M 22 x 1,5 K	15,0	23,5	36	31	24
XWM NW 03 HS	S	PN 400	6	M 12 x 1,5 K	12,0	16,0	26	23	12
XWM NW 04 HS	S	PN 400	8	M 14 x 1,5 K	12,0	17,0	27	24	14
XWM NW 06 HS	S	PN 400	10	M 16 x 1,5 K	12,0	17,5	28	25	17
XWM NW 08 HS	S	PN 400	12	M 18 x 1,5 K	12,0	21,5	28	29	17
XWM NW 10 HS	S	PN 400	14	M 20 x 1,5 K	14,0	22,0	32	30	19
XWM NW 13 HS	S	PN 400	16	M 22 x 1,5 K	14,0	24,5	32	33	24

seriya: LL = zelo lahko L = lahko S = težko -- PN = nazivni tlak PB = maks. obratovalni tlak -- Ø d2 = zunanji premer cevi

Variante izdelka

XWMK VA	Vijačni priključek na uvoj, kot 90°, nerjavno jeklo
WMK	Vijačni priključek na uvoj, kot 90°, jeklo