

G AB HB VA

Spojniki

HANSA FLEX

Lastnosti

| | |
|------------------|-------------------------------|
| Priključek 1 | matični navoj BSP |
| Oblika tesnila 1 | 60° zunanji konus |
| Priključek 2 | zunanji navoj cilindrični BSP |
| Oblika tesnila 2 | 60° notranji konus |
| Način izdelave | vezniki |
| Oblika izdelave | ravno |
| Material: | nerjavno jeklo |



Artikel

| Opis | G1 | G2 | SW (mm) | S1 |
|------------------|--------------|--------------|------------|----|
| G AB 02 HB VA | G 1/8" -28 | G 1/8" -28 | 14 | 14 |
| G AB 02 HB 04 VA | G 1/8" -28 | G 1/4" -19 | 19 | 19 |
| G AB 04 HB 02 VA | G 1/4" -19 | G 1/8" -28 | 19 | 19 |
| G AB 04 HB VA | G 1/4" -19 | G 1/4" -19 | 19 | 19 |
| G AB 04 HB 06 VA | G 1/4" -19 | G 3/8" -19 | 22 | 19 |
| G AB 04 HB 08 VA | G 1/4" -19 | G 1/2" -14 | 27 | 19 |
| G AB 06 HB 02 VA | G 3/8" -19 | G 1/8" -28 | 22 | 14 |
| G AB 06 HB 04 VA | G 3/8" -19 | G 1/4" -19 | 19 | 22 |
| G AB 06 HB VA | G 3/8" -19 | G 3/8" -19 | 22 | 22 |
| G AB 06 HB 08 VA | G 3/8" -19 | G 1/2" -14 | 27 | 22 |
| G AB 08 HB 04 VA | G 1/2" -14 | G 1/4" -19 | 19 | 27 |
| G AB 08 HB 06 VA | G 1/2" -14 | G 3/8" -19 | 22 | 27 |
| G AB 08 HB VA | G 1/2" -14 | G 1/2" -14 | 27 | 27 |
| G AB 08 HB 12 VA | G 1/2" -14 | G 3/4" -14 | 32 | 27 |
| G AB 12 HB 08 VA | G 3/4" -14 | G 1/2" -14 | 27 | 32 |
| G AB 12 HB VA | G 3/4" -14 | G 3/4" -14 | 32 | 32 |
| G AB 12 HB 16 VA | G 3/4" -14 | G 1" -11 | 41 | 32 |
| G AB 16 HB 12 VA | G 1" -11 | G 3/4" -14 | 41 | 36 |
| G AB 16 HB VA | G 1" -11 | G 1" -11 | 41 | 41 |
| G AB 16 HB 20 VA | G 1" -11 | G 1,1/4" -11 | 41 | 46 |
| G AB 20 HB 16 VA | G 1,1/4" -11 | G 1" -11 | 46 | 41 |
| G AB 20 HB VA | G 1,1/4" -11 | G 1,1/4" -11 | 50 | 50 |
| G AB 24 HB VA | G 1,1/2" -11 | G 1,1/2" -11 | 55 | 55 |
| G AB 32 HB VA | G 2" -11 | G 2" -11 | 70 | 70 |

SW, S1, S2 = ključna širina

Variante izdelka

G AB HB Spojniki, jeklo