


G AN HN

Uvojni cevni nastavek

Lastnosti

| | |
|------------------|--------------------------|
| Priključek 1 | NPT-matični navoj (NPSM) |
| Oblika tesnila 1 | 60° zunanji konus |
| Priključek 2 | Zunanji navoj NPT |
| Oblika tesnila 2 | tesni navoje |
| Način izdelave | uvojni cevni nastavek |
| Oblika izdelave | ravno |
| Material: | jeklo |
| Zaščita površine | galvanično prevlečeno |



Artikel

| Opis | G1 | G2 | SW (mm) | S1 |
|---------------|------------------|------------------|------------|----|
| G AN 02 HN | 1/8" -27 NPT | 1/8" -27 NPT | 14 | 14 |
| G AN 04 HN | 1/4" -18 NPT | 1/4" -18 NPT | 18 | 18 |
| G AN 04 HN 02 | 1/4" -18 NPT | 1/8" -27 NPT | 16 | 18 |
| G AN 04 HN 06 | 1/4" -18 NPT | 3/8" -18 NPT | 18 | 18 |
| G AN 06 HN | 3/8" -18 NPT | 3/8" -18 NPT | 22 | 22 |
| G AN 06 HN 04 | 3/8" -18 NPT | 1/4" -18 NPT | 21 | 22 |
| G AN 06 HN 08 | 3/8" -18 NPT | 1/2" -14 NPT | 22 | 22 |
| G AN 08 HN | 1/2" -14 NPT | 1/2" -14 NPT | 25 | 25 |
| G AN 08 HN 04 | 1/2" -14 NPT | 1/4" -18 NPT | 24 | 25 |
| G AN 08 HN 06 | 1/2" -14 NPT | 3/8" -18 NPT | 24 | 25 |
| G AN 08 HN 12 | 1/2" -14 NPT | 3/4" -14 NPT | 29 | 25 |
| G AN 12 HN | 3/4" -14 NPT | 3/4" -14 NPT | 32 | 32 |
| G AN 12 HN 08 | 3/4" -14 NPT | 1/2" -14 NPT | 32 | 32 |
| G AN 12 HN 16 | 3/4" -14 NPT | 1" -11,5 NPT | 35 | 38 |
| G AN 16 HN | 1" -11,5 NPT | 1" -11,5 NPT | 38 | 38 |
| G AN 16 HN 12 | 1" -11,5 NPT | 3/4" -14 NPT | 38 | 38 |
| G AN 20 HN | 1,1/4" -11,5 NPT | 1,1/4" -11,5 NPT | 48 | 48 |
| G AN 24 HN 16 | 1,1/2" -11,5 NPT | 1" -11,5 NPT | 45 | 54 |
| G AN 24 HN | 1,1/2" -11,5 NPT | 1,1/2" -11,5 NPT | 54 | 54 |
| G AN 32 HN | 2" -11,5 NPT | 2" -11,5 NPT | 67 | 67 |

SW, S1, S2 = ključna širina