


Lastnosti

| | |
|-------------------------|--------------------------|
| Priključek 1 | NPT-matični navoj (NPSM) |
| Oblika tesnila 1 | 60° zunanji konus |
| Priključek 2 | notranji navoj NPT |
| Oblika tesnila 2 | tesni navoje |
| Način izdelave | navojni cevni nastavek |
| Oblika izdelave | ravno |
| Material: | jeklo |
| Zaščita površine | galvanično prevlečeno |



Artikel

| Opis | G1 | G2 | SW (mm) | S1 |
|----------------------|------------------|------------------|------------|----|
| G AN 02 IN | 1/8" -27 NPT | 1/8" -27 NPT | 14 | 14 |
| G AN 04 IN | 1/4" -18 NPT | 1/4" -18 NPT | 18 | 18 |
| G AN 06 IN | 3/8" -18 NPT | 3/8" -18 NPT | 22 | 22 |
| G AN 06 IN 04 | 3/8" -18 NPT | 1/4" -18 NPT | 22 | 22 |
| G AN 08 IN 06 | 1/2" -14 NPT | 3/8" -18 NPT | 25 | 22 |
| G AN 08 IN | 1/2" -14 NPT | 1/2" -14 NPT | 25 | 25 |
| G AN 08 IN 12 | 1/2" -14 NPT | 3/4" -14 NPT | 32 | 25 |
| G AN 12 IN | 3/4" -14 NPT | 3/4" -14 NPT | 32 | 32 |
| G AN 16 IN | 1" -11,5 NPT | 1" -11,5 NPT | 38 | 38 |
| G AN 20 IN | 1,1/4" -11,5 NPT | 1,1/4" -11,5 NPT | 48 | 48 |
| G AN 24 IN | 1,1/2" -11,5 NPT | 1,1/2" -11,5 NPT | 54 | 54 |
| G AN 32 IN | 2" -11,5 NPT | 2" -11,5 NPT | 67 | 67 |

SW, S1, S2 = ključna širina