

# G HB IR L

## Navojni cevni nastavek

### Lastnosti

<b>Priključek 1</b>	zunanji navoj cilindrični BSP
<b>Oblika tesnila 1</b>	60° notranji konus
<b>Priključek 2</b>	notranji navoj BSP cilindričen
<b>Oblika tesnila 2</b>	ploščato tesnjenje
<b>Način izdelave</b>	navojni cevni nastavek dolg
<b>Oblika izdelave</b>	ravno
<b>Material:</b>	jeklo
<b>Zaščita površine</b>	galvanično prevlečeno



### Artikel

Opis	G1	G2	i (mm)	L1 (mm)	SW (mm)
<b>G HB 06 IR 04 L</b>	G 3/8" -19	G 1/4" -19	12,0	30,5	22
<b>G HB 08 IR 06 L</b>	G 1/2" -14	G 3/8" -19	16,0	38,0	30
<b>G HB 16 IR 08 L</b>	G 1" -11	G 1/2" -14	19,0	50,0	41
<b>G HB 16 IR 12 L</b>	G 1" -11	G 3/4" -14	20,5	47,5	41
<b>G HB 20 IR 16 L</b>	G 1,1/4" -11	G 1" -11	20,0	48,0	50
<b>G HB 24 IR 20 L</b>	G 1,1/2" -11	G 1,1/4" -11	22,0	54,5	55

SW = ključna širina