

G HB IR L

Navojni cevni nastavek

Lastnosti

| | |
|-------------------------|--------------------------------|
| Priključek 1 | zunanji navoj cilindrični BSP |
| Oblika tesnila 1 | 60° notranji konus |
| Priključek 2 | notranji navoj BSP cilindričen |
| Oblika tesnila 2 | ploščato tesnjenje |
| Način izdelave | navojni cevni nastavek dolg |
| Oblika izdelave | ravno |
| Material: | jeklo |
| Zaščita površine | galvanično prevlečeno |



Artikel

| Opis | G1 | G2 | i (mm) | L1 (mm) | SW (mm) |
|------------------------|--------------|--------------|-----------|------------|------------|
| G HB 06 IR 04 L | G 3/8" -19 | G 1/4" -19 | 12,0 | 30,5 | 22 |
| G HB 08 IR 06 L | G 1/2" -14 | G 3/8" -19 | 16,0 | 38,0 | 30 |
| G HB 16 IR 08 L | G 1" -11 | G 1/2" -14 | 19,0 | 50,0 | 41 |
| G HB 16 IR 12 L | G 1" -11 | G 3/4" -14 | 20,5 | 47,5 | 41 |
| G HB 20 IR 16 L | G 1,1/4" -11 | G 1" -11 | 20,0 | 48,0 | 50 |
| G HB 24 IR 20 L | G 1,1/2" -11 | G 1,1/4" -11 | 22,0 | 54,5 | 55 |

SW = ključna širina