

# WEO SB HL / WEO SB HS

Vtična os WEO

**HANSA FLEX**

## Lastnosti

|                         |                                     |
|-------------------------|-------------------------------------|
| <b>Priključek 1</b>     | vtična os WEO                       |
| <b>Oblika tesnila 1</b> | zatesni O-tesnilo                   |
| <b>Priključek 2</b>     | metrični zunanji navoj, cilindrični |
| <b>Oblika tesnila 2</b> | 24° notranji konus                  |
| <b>Material:</b>        | jeklo                               |



## Artikel

| Opis                      | Serijska | Ø d2<br>(mm) | Velikost | Obratovalni tlak bar | G1         | Ø D1<br>(mm) | L1<br>(mm) | S1 |
|---------------------------|----------|--------------|----------|----------------------|------------|--------------|------------|----|
| <b>WEO 10 SB NW 06 HL</b> | L        | 8            | 1/4"     | PN 250               | M 14 x 1,5 | 10           | 36         | 19 |
| <b>WEO 13 SB NW 10 HL</b> | L        | 12           | 3/8"     | PN 250               | M 18 x 1,5 | 13           | 40         | 22 |
| <b>WEO 16 SB NW 13 HL</b> | L        | 15           | 1/2"     | PN 250               | M 22 x 1,5 | 16           | 41         | 27 |
| <b>WEO 23 SB NW 20 HL</b> | L        | 22           | 3/4"     | PN 160               | M 30 x 2   | 23           | 54         | 32 |
| <b>WEO 13 SB NW 08 HS</b> | S        | 12           | 3/8"     | PN 350               | M 20 x 1,5 | 13           | 41         | 22 |
| <b>WEO 16 SB NW 13 HS</b> | S        | 16           | 1/2"     | PN 350               | M 24 x 1,5 | 16           | 43         | 27 |
| <b>WEO 23 SB NW 20 HS</b> | S        | 25           | 3/4"     | PN 250               | M 36 x 2   | 23           | 58         | 41 |

Ø d2 = zunanji premer cevi – SW, S1, S2 = ključna širina

## Nadomestni deli

**WEO B DISA** Komplet tesnil WEO