

TKM OV HB

Objemka za temperirno spojko brez ventila

HANSA FLEX

Lastnosti

Priključek 1 zunanji navoj cilindrični BSP

Oblika tesnila 1 60° notranji konus

Material: med



Navodila za naročanje

Druge vrednosti za tlake in temperature na zahtevo.

Artikel

| Opis | DN* | Priključni navoj | Mere vtiča (mm) | Obratovalni tlak (bar) | SF* ozn. * | Temperatura mineralno olje min. (°C) | Temperatura mineralno olje max. (°C) | SW (mm) |
|-----------------|-----|------------------|-----------------|------------------------|------------|--------------------------------------|--------------------------------------|---------|
| TKM 09 OV 06 HB | 6 | G 1/4" -19 | 9 | 15,0 | 3 | -15 | 150 | 17 |
| TKM 09 OV 10 HB | 10 | G 3/8" -19 | 9 | 15,0 | 3 | -15 | 150 | 19 |
| TKM 13 OV 06 HB | 6 | G 1/4" -19 | 13 | 15,0 | 3 | -15 | 150 | 22 |
| TKM 13 OV 10 HB | 10 | G 3/8" -19 | 13 | 15,0 | 3 | -15 | 150 | 22 |
| TKM 19 OV 13 HB | 12 | G 1/2" -14 | 19 | 15,0 | 3 | -15 | 150 | 30 |
| TKM 19 OV 20 HB | 19 | G 3/4" -14 | 19 | 15,0 | 3 | -15 | 150 | 30 |

NP = nazivni premer, nazivna širina – SF pr. = varnostni faktor priključen – SW = ključna širina