

TKM OV HB

Objemka za temperirno spojko brez ventila

HANSA FLEX

Lastnosti

Priključek 1 zunanji navoj cilindrični BSP

Oblika tesnila 1 60° notranji konus

Material: med



Navodila za naročanje

Druge vrednosti za tlake in temperature na zahtevo.

Artikel

Opis	DN*	Priključni navoj	Mere vtiča (mm)	Obratovalni tlak (bar)	SF* ozn. *	Temperatura mineralno olje min. (°C)	Temperatura mineralno olje max. (°C)	SW (mm)
TKM 09 OV 06 HB	6	G 1/4" -19	9	15,0	3	-15	150	17
TKM 09 OV 10 HB	10	G 3/8" -19	9	15,0	3	-15	150	19
TKM 13 OV 06 HB	6	G 1/4" -19	13	15,0	3	-15	150	22
TKM 13 OV 10 HB	10	G 3/8" -19	13	15,0	3	-15	150	22
TKM 19 OV 13 HB	12	G 1/2" -14	19	15,0	3	-15	150	30
TKM 19 OV 20 HB	19	G 3/4" -14	19	15,0	3	-15	150	30

NP = nazivni premer, nazivna širina – SF pr. = varnostni faktor priključen – SW = ključna širina