

# TKS OV HB

Objemka za temperirno sklopko brez ventila

**HANSA FLEX**

## Lastnosti

**Priključek 1** zunanji navoj cilindrični BSP

**Oblika tesnila 1** 60° notranji konus

**Material:** med



## Navodila za naročanje

Druge vrednosti za tlake in temperature na zahtevo.

## Artikel

Opis	DN*	Priključni navoj	Mere vtiča (mm)	Obratovalni tlak (bar)	SF* ozn. *	Temperatura mineralno olje min. (°C)	Temperatura mineralno olje max. (°C)	SW (mm)
TKS 09 OV 02 HB	2	G 1/8" -28	9	15,0	3	-15	150	11
TKS 09 OV 06 HB	6	G 1/4" -19	9	15,0	3	-15	150	15
TKS 09 OV 10 HB	10	G 3/8" -19	9	15,0	3	-15	150	17
TKS 13 OV 06 HB	6	G 1/4" -19	13	15,0	3	-15	150	15
TKS 13 OV 10 HB	10	G 3/8" -19	13	15,0	3	-15	150	17
TKS 13 OV 13 HB	12	G 1/2" -14	13	15,0	3	-15	150	22
TKS 19 OV 13 HB	12	G 1/2" -14	19	15,0	3	-15	150	22
TKS 19 OV 20 HB	19	G 3/4" -14	19	15,0	3	-15	150	27

NP = nazivni premer, nazivna širina – SF pr. = varnostni faktor priključen – SW = ključna širina