

## Lastnosti

**Način izdelave** brezvijačne objemke za cevi

**Material:** nerjaveče kromnikljevo jeklo



## Opis

objemka CLIC za cevi je zanesljiv element za povezovanje priključnih cevnih sistemov.

## Artikel

Opis	Napenjalno območje (mm)	Razpon (mm)
CLIC 11.5-12.5	11,5 - 12,5	7,0
CLIC 12-13	12,0 - 13,0	7,0
CLIC 13-14	12,5 - 14,0	8,0
CLIC 14-15	13,5 - 15,0	8,0
CLIC 15-16	14,5 - 16,0	8,0
CLIC 16-17	15,5 - 17,0	8,0
CLIC 17-18	16,5 - 18,0	8,0
CLIC 18-19	17,5 - 19,0	8,0
CLIC 19-20	18,5 - 20,0	8,0
CLIC 20-21	19,5 - 21,0	8,0
CLIC 20.5-21.5	20,5 - 22,0	8,0
CLIC 21.5-23	21,5 - 23,0	8,0
CLIC 22.5-24	22,5 - 24,0	8,0
CLIC 23.5-25	23,5 - 25,0	8,0
CLIC 25.5-27	25,5 - 27,0	8,0
CLIC 26.5-28	26,5 - 28,0	8,0

## Pribor

**CLIC ZANGE** Klešče za CLIC-objemko