

## Lastnosti

Način izdelave Objemke s polžastim navojem

Način izdelave-dodatek šestrobi vijak z zarezo

Material: legirano jeklo 1.4016



## Navodilo

vijaki iz pocinkanega jekla in rumeno kromirani.

## Artikel

| Opis              | Napenjalno območje (mm) | Razpon (mm) |
|-------------------|-------------------------|-------------|
| ESK 08-12 W2      | 8 - 12                  | 9,0         |
| ESK 10-16 W2      | 10 - 16                 | 9,0         |
| ESK 12-20 W2      | 12 - 20                 | 9,0         |
| ESK 16-25 W2      | 16 - 25                 | 9,0         |
| ESK 20-32 W2      | 20 - 32                 | 9,0         |
| ESK 25-40 W2      | 25 - 40                 | 9,0         |
| ESK 32-50 W2      | 32 - 50                 | 9,0         |
| ESK 40-60 W2      | 40 - 60                 | 9,0         |
| ESK 50-70 W2      | 50 - 70                 | 9,0         |
| ESK 60-80 W2      | 60 - 80                 | 9,0         |
| ESK 70-90 W2      | 70 - 90                 | 9,0         |
| ESK 80-100 W2     | 80 - 100                | 9,0         |
| ESK 90-110 W2     | 90 - 110                | 9,0         |
| ESK 100-120 W2    | 100 - 120               | 9,0         |
| ESK 110-130 W2    | 110 - 130               | 9,0         |
| ESK 120-140 W2    | 120 - 140               | 9,0         |
| ESK 130-150 W2    | 130 - 150               | 9,0         |
| ESK 12 16-25 W2   | 16 - 25                 | 12,0        |
| ESK 12 20-32 W2   | 20 - 32                 | 12,0        |
| ESK 12 25-40 W2   | 25 - 40                 | 12,0        |
| ESK 12 32-50 W2   | 32 - 50                 | 12,0        |
| ESK 12 40-60 W2   | 40 - 60                 | 12,0        |
| ESK 12 50-70 W2   | 50 - 70                 | 12,0        |
| ESK 12 60-80 W2   | 60 - 80                 | 12,0        |
| ESK 12 70-90 W2   | 70 - 90                 | 12,0        |
| ESK 12 80-100 W2  | 80 - 100                | 12,0        |
| ESK 12 90-110 W2  | 90 - 110                | 12,0        |
| ESK 12 100-120 W2 | 100 - 120               | 12,0        |
| ESK 12 110-130 W2 | 110 - 130               | 12,0        |

## Variante izdelka

ESK Cevna objemka, legirano jeklo 1.4301

## Pribor

SCHRAUBENDR Izvijač, upogljiv