

NRS W4 (15 mm)

Pritrdilna objemka

HANSA FLEX

Lastnosti

Območje uporabe	za pritrditev cevi in kablov
Način izdelave	Pipe clamp
Način izdelave-dodatek	s profilom iz gume
Standard	DIN 3016
Material:	kromnikljevo jeklo (1.4301)



Artikel

Opis	najmanjši Ø (mm)	Razpon (mm)	Vrtina Ø (mm)
NRS 05-15 W4	5	15,0	6,4
NRS 06-15 W4	6	15,0	6,4
NRS 07-15 W4	7	15,0	6,4
NRS 08-15 W4	8	15,0	6,4
NRS 09-15 W4	9	15,0	6,4
NRS 10-15 W4	10	15,0	6,4
NRS 11-15 W4	11	15,0	6,4
NRS 12-15 W4	12	15,0	6,4
NRS 13-15 W4	13	15,0	6,4
NRS 14-15 W4	14	15,0	6,4
NRS 15-15 W4	15	15,0	6,4
NRS 16-15 W4	16	15,0	6,4
NRS 17-15 W4	17	15,0	6,4
NRS 18-15 W4	18	15,0	6,4
NRS 19-15 W4	19	15,0	6,4
NRS 20-15 W4	20	15,0	6,4
NRS 21-15 W4	21	15,0	6,4
NRS 22-15 W4	22	15,0	6,4
NRS 23-15 W4	23	15,0	6,4
NRS 24-15 W4	24	15,0	6,4
NRS 25-15 W4	25	15,0	6,4
NRS 26-15 W4	26	15,0	6,4
NRS 27-15 W4	27	15,0	6,4
NRS 28-15 W4	28	15,0	6,4
NRS 29-15 W4	29	15,0	6,4
NRS 30-15 W4	30	15,0	6,4
NRS 31-15 W4	31	15,0	6,4
NRS 32-15 W4	32	15,0	6,4
NRS 33-15 W4	33	15,0	6,4
NRS 34-15 W4	34	15,0	6,4
NRS 35-15 W4	35	15,0	6,4
NRS 36-15 W4	36	15,0	6,4
NRS 37-15 W4	37	15,0	6,4
NRS 38-15 W4	38	15,0	6,4
NRS 39-15 W4	39	15,0	6,4
NRS 40-15 W4	40	15,0	6,4

Variante izdelka

NRS (15 mm)	Pritrdilna objemka, jeklo
NRS (9 mm)	Pritrdilna objemka, jeklo
NRS (12 mm)	Pritrdilna objemka, jeklo
NRS W4 (12 mm)	Pritrdilna objemka, kromnikljevo jeklo (1.4301)
NRS (20 mm)	Pritrdilna objemka, jeklo
NRS W4 (20 mm)	Pritrdilna objemka, kromnikljevo jeklo (1.4301)
NRS (25 mm)	Pritrdilna objemka, jeklo