

SRS IS 30-100

Inbus vijak, enocevna objemka

HANSA FLEX

Lastnosti

| | |
|------------------|-----------------------|
| Način izdelave | za enocevne objemke |
| Serijska | težko |
| Standard | DIN 912 (ISO 4762) |
| Material: | jeklo |
| Zaščita površine | galvanično prevlečeno |



Artikel

| Opis | Velikost objemke | G | L (mm) | SW (mm) |
|------------|------------------|------|-----------|------------|
| SRS IS 30 | 1 | M 10 | 40 | 8 |
| SRS IS 40 | 2 | M 10 | 60 | 8 |
| SRS IS 50 | 3 | M 10 | 70 | 8 |
| SRS IS 60 | 4 | M 12 | 100 | 10 |
| SRS IS 70 | 5 | M 16 | 130 | 14 |
| SRS IS 80 | 6 | M 20 | 190 | 17 |
| SRS IS 90 | 7 | M 24 | 220 | 19 |
| SRS IS 100 | 8 | M 30 | 300 | 22 |

Variante izdelka

SRS IS 30-100 V4 Inbus vijak, enocevna objemka, legirano jeklo 1.4571

je dodatni del za naslednje izdelke

| | |
|-----|--------------------------|
| C | Sestava skupine C |
| C D | Sestava skupine C dvojno |