

# WA VC

priključek ... VC, temprana litina

**HANSA FLEX**

## Lastnosti

<b>Območje uporabe</b>	Priključna armatura za kovinske cevi
<b>Priključek 1</b>	konični colski zunanji navoj
<b>Oblika tesnila 1</b>	konično tesnenje
<b>Standard</b>	DIN EN 10226 / ISO 7-1
<b>Uporaba</b>	lotana izvedba, obstojna do 200 °C
<b>Oblika izdelave</b>	ravno
<b>Izvedba</b>	3-delni navoj
<b>Material:</b>	temprana litina



## Navodilo

Navedene so orientacijske vrednosti!

The specified working pressure PN(bar) relates to the working temperature of -20 °C to 120 °C. At working temperature of 120 °C to 200 °C the working pressure PN (bar) reduces to 22,7 bar.

## Navodila za naročanje

Druge izvedbe na zahtevo

## Artikel

Opis	DN	PN (bar)	G1	S1 (mm)
WA 006 VC	6	25	R 1/4"	28,0
WA 010 VC	10	25	R 3/8"	32,0
WA 013 VC	13	25	R 1/2"	39,0
WA 020 VC	20	25	R 3/4"	48,0
WA 025 VC	25	25	R 1"	55,0
WA 032 VC	32	25	R 1.1/4"	67,0
WA 040 VC	40	25	R 1.1/2"	74,0
WA 050 VC	50	25	R 2"	90,0

## Variante izdelka

WA VC RG	priključek ... VC, rdeča litina, Rdeča litina
WA VC VA	priključek ... VC, VA, nerjavno jeklo