


## Lastnosti

Način izdelave	O-ring
Način izdelave-dodatek	Standard AS / BS
Barva	BOX, rdeča
Temperatura min.	-30 °C
Temperatura max.	100 °C
Temperatura FPM min.	-15 °C
Temperatura FPM max.	200 °C



D x d	Menge / Quantity	D x d	Menge / Quantity
20,35 x 1,78	15	34,52 x 3,53	10
21,95 x 1,78	15	36,10 x 3,53	10
25,07 x 2,62	15	37,69 x 3,53	10
26,64 x 2,62	15	40,87 x 3,53	10
28,25 x 2,62	15	40,04 x 3,53	10
29,82 x 2,62	15	47,22 x 3,53	10
31,42 x 2,62	10	50,40 x 3,53	10
33,00 x 2,62	10	37,47 x 5,34	10
34,59 x 2,62	10	40,65 x 5,34	10
29,75 x 3,53	15	43,82 x 5,34	10
31,34 x 3,53	15	47,00 x 5,34	5
32,92 x 3,53	15	50,16 x 5,34	5

## Opis

BOX B sestavlja 24 odmerkov - 275 kosov

## Artikel

Opis	Material:	Predali
BOX B	NBR 70 Shore A	24
BOX B FPM80	FPM 80 Shore A	24
BOX B NBR90	NBR 90 Shore A	24