

# XV RD HB OS

Sejalni priključek

**HANSA FLEX**

## Lastnosti

**Območje uporabe** za gradnjo, rudarstvo in tunele

**Priključek 1** okrogel zunanji navoj

**Priključek 2** zunanji navoj cilindrični BSP

**Standard** DIN 20037

**Sredstva** stisnjen zrak, voda

**Material:** jeklo



## Opis

Primerno za vijalne priključke s konusno tulko

## Artikel

Opis	Izvedba	G1	G2	dolžina (mm)	Konus	SW (mm)	Obratovalni tlak bar
XVRD 32 HB 20 OS	brez sita	Rd 32 x 1/8"	G 3/4" -14	48	1:3	32	PN 25
XVRD 38 HB 25 OS	brez sita	Rd 38 x 1/8"	G 1" -11	54	1:3	41	PN 25
XVRD 46 HB 25 OS	brez sita	Rd 46 x 1/6"	G 1" -11	58	1:3	46	PN 25
XVRD 46 HB 32 OS	brez sita	Rd 46 x 1/6"	G 1,1/4" -11	58	1:3	46	PN 25
XVRD 46 HB 40 OS	brez sita	Rd 46 x 1/6"	G 1,1/2" -11	63	1:3	50	PN 25
XVRD 55 HB 32 OS	brez sita	Rd 55 x 1/6"	G 1,1/4" -11	63	1:3	55	PN 25
XVRD 55 HB 40 OS	brez sita	Rd 55 x 1/6"	G 1,1/2" -11	68	1:3	55	PN 25
XVRD 55 HB 50 OS	brez sita	Rd 55 x 1/6"	G 2" -11	68	1:3	75	PN 25
XVRD 62 HB 40 OS	brez sita	Rd 62 x 1/6"	G 1,1/2" -11	75	1:3	65	PN 25
XVRD 62 HB 50 OS	brez sita	Rd 62 x 1/6"	G 2" -11	75	1:3	75	PN 25
XVRD 75 HB 40 OS	brez sita	Rd 75 x 1/6"	G 1,1/2" -11	80	1:3	75	PN 25
XVRD 75 HB 50 OS	brez sita	Rd 75 x 1/6"	G 2" -11	85	1:3	75	PN 25

G1 - G2 = navoj priključkov 1 oz. 2 - SW = ključna širina