

# PRT M HR

Perrot-spojka, ženski del, zunanji navoj

**HANSA FLEX**

## Lastnosti

Priključek 1	ženski del spojke
Oblika tesnila 1	zatesni O-tesnilo
Priključek 2	zunanji navoj cilindrični BSP
Material:	jeklo
Zaščita površine	v ognju pocinkano



## Artikel

Opis	Obratovalni tlak (bar)	Mera spojke (mm)	G1
PRT M 50 HR 1.1/2	12,0	50,0	G 1,1/2" -11
PRT M 50 HR 2	12,0	50,0	G 2"
PRT M 50 HR 2.1/2	12,0	50,0	G 2,1/2" -11
PRT M 70 HR 2	12,0	70,0	G 2"
PRT M 70 HR 2.1/2	12,0	70,0	G 2,1/2" -11
PRT M 70 HR 3	12,0	70,0	G 3" -11
PRT M 89 HR 2.1/2	12,0	89,0	G 2,1/2" -11
PRT M 89 HR 3	12,0	89,0	G 3" -11
PRT M 108 HR 2.1/2	12,0	108,0	G 2,1/2" -11
PRT M 108 HR 3	12,0	108,0	G 3" -11
PRT M 108 HR 4	12,0	108,0	G 4" -11
PRT M 133 HR 2.1/2	12,0	133,0	G 2,1/2" -11
PRT M 133 HR 4	12,0	133,0	G 4" -11
PRT M 133 HR 5	12,0	133,0	G 5" -11
PRT M 159 HR 2.1/2	12,0	159,0	G 2,1/2" -11
PRT M 159 HR 4	12,0	159,0	G 4" -11
PRT M 159 HR 6	12,0	159,0	G 6" -11