


HK GEH 30 GGG

Ohišje ventila za navojni ventil SAE 3-potni GGG 40

HANSA FLEX

Lastnosti

Material:	GGG 40
Obratovalni tlak	maks. 350 bar
Zaščita površine	pocinkano



Artikel

Opis	Vrtina za ventil	A	Priključek 1,3	Priključek 3	C	D	E	F	G	G1	H	I	L	M	Teža
					(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)
HK GEH 38 C0830 GGG	C0830	UNF 3/4"	G 3/8"	G 3/8"	60	65	29	30,0	29,5	15,0	15	7	7,5	44	0,6
HK GEH 38 C1030 GGG	C1030	UNF 7/8"	G 3/8"	G 3/8"	70	75	39	35,5	34,5	18,5	15	7	7,5	54	1,2
HK GEH 12 C1230 GGG	C1230	UNF 1,1/16"	G 3/4"	G 1/2"	80	100	39	40,0	53,5	28,5	18	9	10,0	59	1,7

je pribor za naslednje izdelke

HK BFCV	3-potni ventil za regulacijo pretoka BFCV
HK PRRS	3-potni reducirni ventil, PRRS