

WFG JIC (3000 PSI)

Adapter za spojko SAE, kovano

HANSA FLEX

Lastnosti

Tlačna vrsta	3000 psi
Standard	SAE J 518 C ISO 6162
Način izdelave-dodatek	kovano
Oblika izdelave	koleno 90°
Način izdelave	adapter SAE-prirobnica
Obseg dobave	samo prirobnica
Material:	S355J2G3 (ST52.3)
Zaščita površine	galvanično prevlečeno



Navodilo

Navedeni najvišji obratovalni tlak velja za prirobnico! Dejanski obratovalni tlak se določa na osnovi cevi (debeline stene) in na osnovi kvalitete cevi!

Priporočeni vijaki so navedeni v stolpcih M (metr) ali M (unc).

Artikel

Opis	PB 10.9 (bar)	Velikost	A	B1 (mm)	B2 (mm)	E (mm)	F1 (mm)	S1 (mm)	S2 (mm)	L (mm)	M metr.	M unc
WFG 3001 JIC 3/4	350	1/2"	UNF 3/4"	9,9	13	17,5	60,8	38	38	8,7	M 8 x 25	5/16" x 1.1/4"
WFG 3001 JIC 7/8	350	1/2"	UNF 7/8"	12,3	13	17,5	60,8	38	38	8,7	M 8 x 25	5/16" x 1.1/4"
WFG 3002 JIC 1 1/16	350	3/4"	UNF 1,1/16"	15,5	19	22,2	70,9	42	45	10,7	M 10 x 30	3/8" x 1.1/2"
WFG 3002 JIC 1 5/16	350	3/4"	UN 1,5/16"	21,5	19	22,2	70,9	42	45	10,7	M 10 x 30	3/8" x 1.1/2"
WFG 3002 JIC 7/8	350	3/4"	UNF 7/8"	12,3	19	22,2	70,9	42	45	10,7	M 10 x 30	3/8" x 1.1/2"
WFG 3003 JIC 1 1/16	315	1"	UNF 1,1/16"	15,5	24	26,2	79,2	45	50	10,7	M 10 x 30	3/8" x 1.1/2"
WFG 3003 JIC 1 5/16	315	1"	UN 1,5/16"	21,5	24	26,2	79,2	45	50	10,7	M 10 x 30	3/8" x 1.1/2"
WFG 3003 JIC 1 5/8	315	1"	UN 1,5/8"	27,5	24	26,2	79,2	45	50	10,7	M 10 x 30	3/8" x 1.1/2"
WFG 3004 JIC 1 5/16	250	1.1/4"	UN 1,5/16"	21,5	31	30,2	85,3	50	59	*1	*2	7/16" x 1.1/2"
WFG 3004 JIC 1 5/8	250	1.1/4"	UN 1,5/8"	27,5	31	30,2	85,3	50	59	*1	*2	7/16" x 1.1/2"
WFG 3005 JIC 1 5/8	200	1.1/2"	UN 1,5/8"	27,5	38	35,7	117,1	76	76	13,5	M 12 x 35	1/2" x 1.1/2"
WFG 3005 JIC 1 7/8	200	1.1/2"	UN 1,7/8"	33,0	38	35,7	117,1	76	76	13,5	M 12 x 35	1/2" x 1.1/2"

PN = nazivni tlak PB = maks. obratovalni tlak

*1) = po izbiri 10,5, 12,0 ali 12,5 – *2) = izbirno M 10 x 30 ali M 12 x 35

Variante izdelka

WFG JIC U (3000 / 6000 PSI) Adapter za spojko SAE, kovano, z 2 polprirobnicama, kompletom vijakov in O-tesnilom

WFG JIC M (3000 / 6000 PSI) Adapter za spojko SAE, kovano, z 2 polprirobnicama, kompletom vijakov in O-tesnilom