

## Lastnosti

|                  |                        |
|------------------|------------------------|
| Način izdelave   | mehko tesnilo          |
| Oblika izdelave  | ISO 8434-2             |
| Material:        | nerjavno jeklo         |
| Zaščita površine | sealing varnish coated |



## Opis

Dodatna zatesnitev priključkov HJ in AJ (37°).

## Artikel

| Opis        | Size | za navoj       |
|-------------|------|----------------|
| WD 03 HJ VA | 3    | 3/8" -24 UNF   |
| WD 04 HJ VA | 4    | 7/16" -20 UNF  |
| WD 05 HJ VA | 5    | 1/2" -20 UNF   |
| WD 06 HJ VA | 6    | 9/16" -18 UNF  |
| WD 08 HJ VA | 8    | 3/4" -16 UNF   |
| WD 10 HJ VA | 10   | 7/8" -14 UNF   |
| WD 12 HJ VA | 12   | 1.1/16" -12 UN |
| WD 14 HJ VA | 14   | 1.3/16" -12 UN |
| WD 16 HJ VA | 16   | 1.5/16" -12 UN |
| WD 20 HJ VA | 20   | 1.5/8" -12 UN  |
| WD 24 HJ VA | 24   | 1.7/8" -12 UN  |
| WD 32 HJ VA | 32   | 2.1/2" -12 UN  |