

## Lastnosti

<b>Priključek 1</b>	prosta prirobnica v tlačnem razredu PN16
<b>Oblika izdelave</b>	ravno
<b>Oblika tesnila 1</b>	ploščato tesnenje
<b>Območje uporabe</b>	Industrija
<b>Standard</b>	DIN EN 1092-1
<b>Material:</b>	nerjavno jeklo



## Artikel

Opis	DN*	Size	Palec	Ø D (mm)	K (mm)	Ø d2 (mm)	N (mm)
TUE G 25 LF PN16 VA	25	16	1"	115,0	85	14	4
TUE G 32 LF PN16 VA	32	20	1.1/4"	140,0	100	18	4
TUE G 38 LF PN16 VA	40	24	1.1/2"	150,0	110	18	4
TUE G 50 LF PN16 VA	50	32	2"	165,0	125	18	4
TUE G 63 LF PN16 VA	63	40	2.1/2"	185,0	145	18	4
TUE G 75 LF PN16 VA	75	50	3"	200,0	160	18	8
TUE G 102 LF PN16 VA	100	64	4"	220,0	180	18	8

N = število lukenj

## Pribor

<b>KS AL</b>	Spojna objemka, aluminij
<b>KS FIX AL</b>	Spojna objemka za povezavo z zatiči, aluminij

## Dodatni elementi

<b>FD C4400</b>	Ploščato tesnilo
-----------------	------------------