

# K-PUR-BREMSSPIRALE

PUR brake coil with connection

**HANSA FLEX**

## Lastnosti

|                         |   |
|-------------------------|---|
| <b>Priključek 1 + 2</b> | metrični zunanji navoj, cilindrični   |
| <b>Standard</b>         | tested in accordance with<br>DIN 74323<br>DIN 74324<br>ISO 7268-2<br>ISO 7375-2<br>DIN 73378<br>DIN 74310-2 |
| <b>Dovoljenje</b>       | German Technical Surveyance Association (TÜV)-<br>type approved (Certificate R 9910199)                     |
| <b>Temperatura min.</b> | -40 °C  |
| <b>Temperatura max.</b> | 90 °C   |
| <b>Material:</b>        | PUR   |



## Dodatne informacije

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

## Artikel

| Opis           | G1 + G2    | Notranji Ø<br>(mm) | Zunanji Ø<br>(mm) | debelina stene<br>(mm) | dolžina<br>(m) | Barva  |
|----------------|------------|--------------------|-------------------|------------------------|----------------|--------|
| K- 07 10 13 21 | M 16 x 1,5 | 8,0                | 12,0              | 2,0                    | 4,50           | črno   |
| K- 07 10 13 22 | M 16 x 1,5 | 8,0                | 12,0              | 2,0                    | 4,50           | rumeno |
| K- 07 10 13 23 | M 16 x 1,5 | 8,0                | 12,0              | 2,0                    | 4,50           | rdeče  |
| K- 07 10 13 24 | M 16 x 1,5 | 8,0                | 12,0              | 2,0                    | 5,50           | črno   |
| K- 07 10 13 25 | M 16 x 1,5 | 8,0                | 12,0              | 2,0                    | 5,50           | rumeno |
| K- 07 10 13 26 | M 16 x 1,5 | 8,0                | 12,0              | 2,0                    | 5,50           | rdeče  |