

# K-FLAMM SCHLAUCH

Flame tube

**HANSA FLEX**


## Lastnosti

**Območje uporabe** welding equipment  
welding robots  
welding machines  
Welding Related areas

**Barva** črno

**Temperatura min.** -40 °C

**Temperatura max.** 90 °C



## Dodatne informacije

- Flame retardant according to UL94 V2/V0
- Welding-spark resistant
- Halogen-free according to EN 50267-2-1 (complies with IEC 60754-1)
- LABS free (free from paint-adhesion inhibiting substances)
- UV-resistant
- can be used with drag chains
- flexible
- resistant to bending
- very good wear resistance
- plasticiser free

## Artikel

| Opis           | Notranji Ø (mm) | Zunanji Ø (mm) | debelina stene (mm) | Polmer upogiba min. (mm) | Max. working pressure resistance at 23°C (bar) | Dolžina valjev (m) |
|----------------|-----------------|----------------|---------------------|--------------------------|--|--------------------|
| K- 07 10 13 27 | 2,0             | 4,0            | 1,0                 | 7                        | 27   | 50                 |
| K- 07 10 13 28 | 4,0             | 6,0            | 1,0                 | 8                        | 20   | 50                 |
| K- 07 10 13 29 | 4,0             | 8,0            | 2,0                 | 9                        | 23   | 50                 |
| K- 07 10 13 30 | 6,0             | 10,0           | 2,0                 | 15                       | 21   | 50                 |
| K- 07 10 13 31 | 8,0             | 12,0           | 2,0                 | 26                       | 18   | 50                 |
| K- 07 10 13 32 | 10,0            | 14,0           | 2,0                 | 38                       | 13   | 50                 |
| K- 07 10 13 33 | 11,0            | 16,0           | 2,5                 | 65                       | 15   | 50                 |