

K-DMUF GENAUIGKEIT 0,2%

Pressure transmitters, accuracy 0.2% of span

HANSA FLEX

Lastnosti

tip	S-10
napetost	Non-stabilised 10/30 V DC voltage
Električni priključek	With right-angle connector acc. to DIN EN 175301-803 A
razred zaščite	IP 65 acc. to EN 60529
izhodni signal	4 to 20 mA, 2-wire
nelinearnost	0.2% of span
temperatura medija	-30 °C to +100 °C
temperatura okolice	-20 °C to +80 °C
dell, ki so v stiku z merjeno snovjo	CrNi steel 1.4571
ohišje	CrNi steel 1.4571



Opis

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

Dodatne informacije

Further measuring ranges on request

Pressure converter with flush-mounted membrane for measuring highly viscous and crystalline media on request.

Artikel

Opis	Mersko območje	Navoj
K- 07 20 10 30	-1 / 0.0 bar	G 1/2
K- 07 20 10 31	0 - 0.25 bar	G 1/2
K- 07 20 10 32	0 - 0.4 bar	G 1/2
K- 07 20 10 33	0 - 1.0 bar	G 1/2
K- 07 20 10 34	0 - 4.0 bar	G 1/2
K- 07 20 10 35	0 - 6.0 bar	G 1/2
K- 07 20 10 36	0 - 10.0 bar	G 1/2
K- 07 20 10 37	0 - 16.0 bar	G 1/2
K- 07 20 10 38	0 - 25.0 bar	G 1/2
K- 07 20 10 39	0 - 40.0 bar	G 1/2
K- 07 20 10 40	0 - 60.0 bar	G 1/2
K- 07 20 10 41	0 - 100.0 bar	G 1/2
K- 07 20 10 42	0 - 160.0 bar	G 1/2
K- 07 20 10 43	0 - 250.0 bar	G 1/2
K- 07 20 10 44	0 - 400.0 bar	G 1/2
K- 07 20 10 45	0 - 600.0 bar	G 1/2