

K-KFMM U MBAR

Capsule-type pressure gauges, connection radial on bottom

HANSA FLEX

Lastnosti

tip	611.10 (Ø 63), 612.20 (Ø 100)
Izvedba	Capsule-type pressure gauge
Uporaba	For gaseous, dry, non-corrosive media
kval.razred	1,6
temperatura medija	max. +100 °C
temperatura okolice	-20 °C do +60 °C
ohišje	Steel, black (Ø 63 mm)CrNi steel (Ø 100 mm)
material merilnega člena in kazalnega mehanizma	bakrova zlitina
kontrolno okence	Plexiglass (Ø 63 mm), flat instrument glass (Ø 100 mm)



Navodilo

Drugi podatki na zahtevo.

Opis

With zero correction

Artikel

Opis	Mersko območje	Ø (mm)	Priključek
K- 07 20 06 88	-160 / 0 mbar	63,0	G 1/4"
K- 07 20 06 89	-100 / 0 mbar	63,0	G 1/4"
K- 07 20 06 90	-60 / 0 mbar	63,0	G 1/4"
K- 07 20 06 91	0 - 40 mbar	63,0	G 1/4"
K- 07 20 06 92	0 - 60 mbar	63,0	G 1/4"
K- 07 20 06 93	0 - 100 mbar	63,0	G 1/4"
K- 07 20 06 94	0 - 160 mbar	63,0	G 1/4"
K- 07 20 06 95	0 - 250 mbar	63,0	G 1/4"
K- 07 20 06 96	0 - 400 mbar	63,0	G 1/4"
K- 07 20 01 13	-160 / 0 mbar	100,0	G 1/2"
K- 07 20 01 14	-100 / 0 mbar	100,0	G 1/2"
K- 07 20 01 15	-60 / 0 mbar	100,0	G 1/2"
K- 07 20 01 16	-25 / +15 mbar	100,0	G 1/2"
K- 07 20 01 17	-40 / +20 mbar	100,0	G 1/2"
K- 07 20 01 18	0 - 25 mbar	100,0	G 1/2"
K- 07 20 01 19	0 - 40 mbar	100,0	G 1/2"
K- 07 20 01 20	0 - 60 mbar	100,0	G 1/2"
K- 07 20 01 21	0 - 100 mbar	100,0	G 1/2"
K- 07 20 01 22	0 - 160 mbar	100,0	G 1/2"
K- 07 20 01 23	0 - 250 mbar	100,0	G 1/2"
K- 07 20 01 24	0 - 400 mbar	100,0	G 1/2"