

# K-MANO

Pressure gauges (CrNi steel type / connection on rear)

**HANSA FLEX**

## Lastnosti

|                     |  |
|---------------------|--|
| tip                 | 232.50   |
| Izvedba             | Bourdon-tube pressure gauge, CrNi steel type, all-stainless steel  |
| Uporaba             | For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise |
| kval.razred         | 1,6 (Ø 63 mm), 1,0 (Ø 100 mm)  |
| temperatura medija  | max. +200 °C   |
| temperatura okolice | -40 °C to +60 °C   |
| ohišje              | CrNi steel   |
| kontrolno okence    | Laminated safety glass Ø 63 = Polycarbonate  |



## Navodilo

Drugi podatki na zahtevo.

## Artikel

| Opis           | Mersko območje | Ø (mm) | Priključek |
|----------------|----------------|--------|------------|
| K- 07 20 06 10 | -1 / 0.0 bar   | 63,0   | G 1/4"     |
| K- 07 20 06 11 | 0 - 2.5 bar    | 63,0   | G 1/4"     |
| K- 07 20 06 12 | 0 - 4.0 bar    | 63,0   | G 1/4"     |
| K- 07 20 06 13 | 0 - 6.0 bar    | 63,0   | G 1/4"     |
| K- 07 20 06 14 | 0 - 10.0 bar   | 63,0   | G 1/4"     |
| K- 07 20 06 15 | 0 - 16.0 bar   | 63,0   | G 1/4"     |
| K- 07 20 06 16 | 0 - 25.0 bar   | 63,0   | G 1/4"     |
| K- 07 20 06 17 | 0 - 40.0 bar   | 63,0   | G 1/4"     |
| K- 07 20 06 18 | 0 - 100.0 bar  | 63,0   | G 1/4"     |
| K- 07 20 06 19 | 0 - 250.0 bar  | 63,0   | G 1/4"     |
| K- 07 20 00 53 | 0 - 6.0 bar    | 100,0  | G 1/2"     |
| K- 07 20 00 54 | 0 - 10.0 bar   | 100,0  | G 1/2"     |