K-PRMM ROB U

Robust diaphragm pressure gauges, connection radial on bottom

Lastnosti

tip	422.12 (robust), 432.50 (chemical)
Izvedba	Diaphragm pressure gauge in robust design or for chemical applications
Uporaba	at chemical applications in aggressive environments for gaseous or liquid media,
kval.razred	1,6
temperatura medija	max. +100 °C
temperatura okolice	-20 °C do +60 °C
Ø merilne prirobnice	100 mm
ohišje, obroč	Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications)
merilni člen	CrNi steel
kontrolno okence	Flat instrument glass (robust type), Laminated safety glass (type for chemical applications)
kazalci	Copper alloy (robust type), CrNi steel (type for chemical applications)



Navodilo

Drugi podatki na zahtevo.

Artikel

Opis	Mersko območje	Ø (mm)	Priključek
K- 07 20 10 99	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 11 00	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 11 01	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 11 02	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 11 03	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 11 04	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 11 05	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 11 06	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 11 07	0 - 25.0 bar	100,0	G 1/2"

Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.