

K-PRMM CHEMIE U

Diaphragm pressure gauges for chemical applications, connection radial on bottom

HANSA FLEX

Lastnosti

| | |
|----------------------|--------------------------------------------------------------------------------------------------|
| tip | 422.12 (robust), 432.50 (chemical) |
| Izvedba | Diaphragm pressure gauge in robust design or for chemical applications |
| Uporaba | at chemical applications in aggressive environments for gaseous or liquid media, |
| kval.razred | 1,6 |
| temperatura medija | max. +100 °C |
| temperatura okolice | -20 °C do +60 °C |
| Ø merilne prirobnice | 100 mm |
| ohišje, obroč | Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications) |
| merilni člen | CrNi steel |
| kontrolno okence | Flat instrument glass (robust type), Laminated safety glass (type for chemical applications) |
| kazalci | Copper alloy (robust type), CrNi steel (type for chemical applications) |



Navodilo

Drugi podatki na zahtevo.

Artikel

| Opis | Mersko območje | Ø (mm) | Priključek |
|----------------|----------------|-----------|------------|
| K- 07 20 10 25 | 0 - 6.0 bar | 100,0 | G 1/2" |
| K- 07 20 10 26 | 0 - 10.0 bar | 100,0 | G 1/2" |