

# K-MANO ROB U

Robust pressure gauges, connection radial on bottom

**HANSA FLEX**

## Lastnosti

tip	212.20
Izvedba	Robust Bourdon-tube pressure gauge
Uporaba	For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
kval.razred	1,0
temperatura medija	max. +80 °C
temperatura okolice	-40 °C to +60 °C
ohišje	CrNi steel
merilni člen	Copper alloy ( $\leq 100$ bar), CrNi steel ( $> 100$ bar)
kontrolno okence	Flat instrument glass
kazalci	Copper alloy



## Navodilo

Drugi podatki na zahtevo.

## Dodatne informacije

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

## Artikel

Opis	Mersko območje	Ø (mm)	Priključek
K- 07 20 01 44	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 01 45	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 01 46	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 01 47	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 01 48	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 01 49	-1 / +15.0 bar	100,0	G 1/2"
K- 07 20 01 50	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 01 51	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 01 52	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 01 53	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 01 54	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 01 55	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 01 56	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 01 57	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 01 58	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 01 59	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 01 60	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 01 61	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 01 62	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 01 63	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 01 64	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 01 65	0 - 600.0 bar	100,0	G 1/2"
K- 07 20 01 66	0 - 1000.0 bar	100,0	G 1/2"
K- 07 20 03 24	-1 / 0.0 bar	160,0	G 1/2"
K- 07 20 03 25	0 - 0.6 bar	160,0	G 1/2"
K- 07 20 03 26	0 - 1.0 bar	160,0	G 1/2"
K- 07 20 03 27	0 - 1.6 bar	160,0	G 1/2"
K- 07 20 03 28	0 - 2.5 bar	160,0	G 1/2"
K- 07 20 03 29	0 - 4.0 bar	160,0	G 1/2"
K- 07 20 03 30	0 - 6.0 bar	160,0	G 1/2"
K- 07 20 03 31	0 - 10.0 bar	160,0	G 1/2"
K- 07 20 03 32	0 - 16.0 bar	160,0	G 1/2"
K- 07 20 03 33	0 - 25.0 bar	160,0	G 1/2"
K- 07 20 03 34	0 - 40.0 bar	160,0	G 1/2"
K- 07 20 03 35	0 - 60.0 bar	160,0	G 1/2"
K- 07 20 03 36	0 - 100.0 bar	160,0	G 1/2"
K- 07 20 03 37	0 - 160.0 bar	160,0	G 1/2"



Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.

07.06.2025

HANSA-FLEX AG

www.hansa-flex.com

1

# K-MANO ROB U

Robust pressure gauges, connection radial on bottom

**HANSA FLEX**

## Artikel

Opis	Mersko območje	Ø (mm)	Priključek
K- 07 20 03 38	0 - 250.0 bar	160,0	G 1/2"
K- 07 20 03 39	0 - 400.0 bar	160,0	G 1/2"
K- 07 20 03 40	0 - 600.0 bar	160,0	G 1/2"