

K-MANO ROB H

Robust pressure gauges, connection on rear, eccentric

HANSA FLEX

Lastnosti

tip	212.20
Izvedba	Robust Bourdon-tube pressure gauge
Uporaba	For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
kval.razred	1,0
temperatura medija	max. +80 °C
temperatura okolice	-40 °C to +60 °C
ohišje	CrNi steel
merilni člen	Copper alloy (≤ 100 bar), CrNi steel (> 100 bar)
kontrolno okence	Flat instrument glass
kazalci	Copper alloy



Navodilo

Drugi podatki na zahtevo.

Dodatne informacije

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

Artikel

Opis	Mersko območje	Ø (mm)	Priključek
K- 07 20 01 67	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 01 68	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 01 69	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 01 70	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 01 71	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 01 72	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 01 73	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 01 74	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 01 75	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 01 76	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 01 77	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 01 78	0 - 250.0 bar	100,0	G 1/2"