


K-MANO ABSPH MUF ZAPF

Pressure gauge stopcocks, female - male

HANSA FLEX

Lastnosti

Uporaba	For all pressure gauges with a flat gasket acc. to DIN 16258
tlačno območje	Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures
temperatura	Max. +50 °C
ohišje	Brass with a bare metal surface or stainless steel 1.4571
ročaj	Plastic
preskusna prirobnica	-



Navodilo

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B
K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B

Drugi podatki na zahtevo.

Opis

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Dodatne informacije

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

Artikel

Opis	Navoj	PN (bar)	SW (mm)	Material:
K- 07 20 10 94	G 1/4	6	17	med
K- 07 20 10 95	G 3/8	16	22	med
K- 07 20 10 97	G 1/2	25	27	med
K- 07 20 10 96	G 1/2	25	27	Stainless steel
K- 07 20 10 98	G 1/2	25	27	med