

K-RMM HFR STAHLBLECH CR

Standard pressure gauges with chrome-plated sheet-steel bezel, connection on rear

HANSA FLEX

Lastnosti

tip	111.12
Izvedba	Bourdon-tube pressure gauge, standard design, mounting ring
Uporaba	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
kval.razred	1,6
temperatura medija	maks. +60 °C
temperatura okolice	-20 °C do +60 °C
ohišje	Sheet steel
material merilnega člena in kazalnega mehanizma	bakrova zlitina
kontrolno okence	Transparent plastic



Navodilo

Drugi podatki na zahtevo.

Artikel

Opis	Mersko območje	Ø (mm)	Priključek
K- 07 20 04 37	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 38	0 - 1.0 bar	40,0	G 1/8
K- 07 20 04 39	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 40	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 41	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 42	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 43	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 44	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 45	0 - 25.0 bar	40,0	G 1/8
K- 07 20 04 46	0 - 40.0 bar	40,0	G 1/8
K- 07 20 05 41	-1 / 0.0 bar	50,0	G 1/4
K- 07 20 05 42	0 - 1.0 bar	50,0	G 1/4
K- 07 20 05 43	0 - 1.6 bar	50,0	G 1/4
K- 07 20 05 44	0 - 2.5 bar	50,0	G 1/4
K- 07 20 05 45	0 - 4.0 bar	50,0	G 1/4
K- 07 20 05 46	0 - 6.0 bar	50,0	G 1/4
K- 07 20 05 47	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 48	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 49	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 50	0 - 40.0 bar	50,0	G 1/4