

# K-RMM H KUNSTSTOFF

Standard pressure gauges (with plastic housing / connection on rear, central)

**HANSA FLEX**

## Lastnosti

tip	111.12
Izvedba	Bourdon-tube pressure gauge in standard design
Uporaba	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
kval.razred	1,6
temperatura medija	maks. +60 °C
temperatura okolice	-20 °C do +60 °C
ohišje	Plastic
material merilnega člena in kazalnega mehanizma	bakrova zlitina
kontrolno okence	Transparent plastic



## Navodilo

Drugi podatki na zahtevo.

## Artikel

Opis	Mersko območje	Ø (mm)	Priključek
K- 07 20 04 56	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 57	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 58	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 59	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 60	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 61	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 62	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 63	0 - 25.0 bar	40,0	G 1/8
K- 07 20 04 64	0 - 40.0 bar	40,0	G 1/8
K- 07 20 05 64	-1 / 0.0 bar	50,0	G 1/4
K- 07 20 05 65	0 - 1.0 bar	50,0	G 1/4
K- 07 20 05 66	0 - 1.6 bar	50,0	G 1/4
K- 07 20 05 67	0 - 2.5 bar	50,0	G 1/4
K- 07 20 05 68	0 - 4.0 bar	50,0	G 1/4
K- 07 20 05 69	0 - 6.0 bar	50,0	G 1/4
K- 07 20 05 70	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 71	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 72	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 73	0 - 40.0 bar	50,0	G 1/4
K- 07 20 05 75	0 - 60.0 bar	50,0	G 1/4
K- 07 20 05 74	0 - 100.0 bar	50,0	G 1/4