

K-RMM U STAHL

Standard pressure gauges (sheet steel housing / connection radial on bottom)

HANSA FLEX

Lastnosti

tip	111.10
Izvedba	Bourdon-tube pressure gauge in standard design
Uporaba	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
kval.razred	1.6 (Art. No. K-07200581: 2.5)
temperatura medija	maks. +60 °C
temperatura okolice	-20 °C do +60 °C
ohišje	Sheet steel
material merilnega člena in kazalnega mehanizma	bakrova zlitina
kontrolno okence	Transparent plastic



Navodilo

Drugi podatki na zahtevo.

Artikel

Opis	Mersko območje	Ø (mm)	Priključek
K- 07 20 04 65	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 66	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 67	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 68	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 69	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 70	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 71	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 72	0 - 25.0 bar	40,0	G 1/8
K- 07 20 04 73	0 - 40.0 bar	40,0	G 1/8
K- 07 20 05 76	-1 / 0.0 bar	50,0	G 1/4
K- 07 20 05 77	0 - 1.0 bar	50,0	G 1/4
K- 07 20 05 78	0 - 1.6 bar	50,0	G 1/4
K- 07 20 05 79	0 - 2.5 bar	50,0	G 1/4
K- 07 20 05 80	0 - 4.0 bar	50,0	G 1/4
K- 07 20 05 81	0 - 6.0 bar	50,0	G 1/4
K- 07 20 05 82	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 83	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 84	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 85	0 - 40.0 bar	50,0	G 1/4
K- 07 20 05 86	0 - 60.0 bar	50,0	G 1/4
K- 07 20 05 87	0 - 100.0 bar	50,0	G 1/4
K- 07 20 05 88	0 - 160.0 bar	50,0	G 1/4