

# K-TR PA 12 ROLLE

Plastic pipes on coils, polyamide PA 12

## Lastnosti

|                            |  |
|----------------------------|--|
| <b>delovna temperatura</b> | -60 °C to +100 °C (PA 12)  |
| <b>Lastnosti</b>           | Resistant to corrosion, vibration, impact, ageing, high pressures and heat |
| <b>Material:</b>           | Polyamid PA 12, hard (according to DIN 73378)                              |



## Navodilo

Operating pressure with 2.5 x overpressure safety!

Drugi podatki na zahtevo.

## Opis

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Artikel

| Opis           | Ø cevi znotraj (mm) | Ø cevi zunaj (mm) | maks. delovni tlak pri 20°C (bar) | Dolžina valjev (m) |
|----------------|---------------------|-------------------|-----------------------------------|--------------------|
| K- 07 10 04 77 | 9,0                 | 12,0              | 19                                | 25                 |
| K- 07 10 04 79 | 12,0                | 15,0              | 15                                | 25                 |
| K- 07 10 04 81 | 14,0                | 18,0              | 16                                | 25                 |
| K- 07 10 04 83 | 18,0                | 22,0              | 14                                | 25                 |
| K- 07 10 04 76 | 9,0                 | 12,0              | 19                                | 100                |
| K- 07 10 04 78 | 12,0                | 15,0              | 15                                | 100                |
| K- 07 10 04 80 | 14,0                | 18,0              | 16                                | 100                |
| K- 07 10 04 82 | 18,0                | 22,0              | 14                                | 100                |
| K- 07 10 04 84 | 23,0                | 28,0              | 14                                | 50                 |