

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Lastnosti

delovna temperatura	-60 °C to +100 °C (PA 12)
Lastnosti	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Dolžina cevi	3 m
Embalažna enota	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Material:	Polyamid PA 12, hard (according to DIN 73378)



Navodilo

Operating pressure with 2.5 x overpressure safety!

Drugi podatki na zahtevo.

Opis

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Artikel

Opis	Zunanji Ø cevi (mm)	notranji Ø cevi (mm)	maks. delovni tlak pri 20°C (bar)	Barva
K- 07 10 04 56	12	9	38	modro
K- 07 10 04 58	12	9	38	črno
K- 07 10 04 60	15	12	25	modro
K- 07 10 04 62	15	12	25	črno
K- 07 10 04 64	18	14	28	modro
K- 07 10 04 66	18	14	28	črno
K- 07 10 04 68	22	18	22	modro
K- 07 10 04 70	22	18	22	črno
K- 07 10 04 72	28	23	20	modro
K- 07 10 04 74	28	23	20	črno