# K-HRF HEBELSTECKER

Handheld tyre gauges with tyre valve connector



## Navodilo

Drugi podatki na zahtevo.

## Opis

Single-lever operation: Inflation, deflation and checking with a single handle. To check - lever in home position. To deflate - lever actuated half-way. To inflate - lever fully actuated. High-quality, concentric pressure gauge 80 mm Ø. Available for the following measuring ranges: 0 to 4 bar/50 psi, 0 to 10 bar/140 psi, 0 to 25 bar/350 psi. These pressure gauges are effectively protected against shock and impact by means of a free-standing plastic cap. They can be loaded against gauge pressure and up to the maximum scale value. With push-in plug for DN 7.2 coupling.

## Artikel

| Opis | Mersko območje | Navodilo |
|---|---|---|
| **K- 07 10 04 10** | 0 bis 4 bar/56 psi | Calibrated |
| **K- 07 10 04 11** | 0 bis 4 bar/56 psi | Uncalibrated |
| **K- 07 10 04 12** | 0 bis 12 bar/170 psi | Calibrated |
| **K- 07 10 04 13** | 0 bis 12 bar/170 psi | Uncalibrated |
| **K- 07 10 04 14** | 0 bis 25 bar/350 psi | Uncalibrated |

*Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.*