

# K-SPIR SCHL B DREH VERSCHRAU

Spiral hose, with swivel adapter fitted at both ends and kink protector

**HANSA FLEX**

## Lastnosti

|                     |  |
|---------------------|--|
| Uporaba             | Air, gases, oils, greases, fuels, organic and inorganic substances |
| delovna temperatura | -40 °C to +100 °C  |
| vrsta priključka    | connection nipples and coupling NW 7,2                             |



## Navodilo

Drugi podatki na zahtevo.

## Opis

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Artikel

| Opis           | Ø cevi znotraj<br>(mm) | Ø cevi zunaj<br>(mm) | Navoj | Ø spirale zunaj<br>(mm) | navitja | Max. working pressure resistance at 23°C<br>(bar) | maks. delovna dolžina<br>(m) |
|----------------|------------------------|----------------------|-------|-------------------------|---------|---|------------------------------|
| K- 07 10 07 34 | 3,1                    | 4,7                  | R 1/8 | 38                      | 36      | 22  | 2,5                          |
| K- 07 10 07 35 | 3,1                    | 4,7                  | R 1/8 | 38                      | 72      | 22  | 5,0                          |
| K- 07 10 07 36 | 3,1                    | 4,7                  | R 1/8 | 38                      | 108     | 22  | 7,5                          |
| K- 07 10 07 37 | 4,8                    | 6,3                  | R 1/4 | 75                      | 15      | 16  | 2,5                          |
| K- 07 10 07 38 | 4,8                    | 6,3                  | R 1/4 | 75                      | 30      | 16  | 5,0                          |
| K- 07 10 07 39 | 4,8                    | 6,3                  | R 1/4 | 75                      | 45      | 16  | 7,5                          |
| K- 07 10 07 40 | 6,3                    | 7,9                  | R 1/4 | 75                      | 15      | 13  | 2,5                          |
| K- 07 10 07 41 | 6,3                    | 7,9                  | R 1/4 | 75                      | 30      | 13  | 5,0                          |
| K- 07 10 07 42 | 6,3                    | 7,9                  | R 1/4 | 75                      | 45      | 13  | 7,5                          |
| K- 07 10 07 28 | 7,9                    | 9,5                  | R 1/4 | 115                     | 10      | 12  | 2,5                          |
| K- 07 10 07 29 | 7,9                    | 9,5                  | R 1/4 | 115                     | 20      | 12  | 5,0                          |
| K- 07 10 07 30 | 7,9                    | 9,5                  | R 1/4 | 115                     | 30      | 12  | 7,5                          |
| K- 07 10 07 31 | 9,5                    | 11,8                 | R 3/8 | 140                     | 8       | 11  | 2,5                          |
| K- 07 10 07 32 | 9,5                    | 11,8                 | R 3/8 | 140                     | 15      | 11  | 5,0                          |
| K- 07 10 07 33 | 9,5                    | 11,8                 | R 3/8 | 140                     | 23      | 11  | 7,5                          |

## Pribor

|                          |                                     |
|--------------------------|-------------------------------------|
| K-DREHBARE VERSCHR KNICK | Swivel adapters with kink protector |
| K-STARRE VERSCHRAUBUNG   | Rigid adapters with kink protector  |